Extract of the Architectural and Engineering Guidelines issued by India Trade Promotion Organization (ITPO) to be strictly followed by all participating agencies in the Fairs organized by ITPO, which also include condition from CCPS "Guidelines on use of glass in Buildings-Human Safety"

INDIA TRADE PROMOTION ORGANISATION (ITPO), PRAGATI BHAWAN, PRAGATI MAIDAN, NEW DELHI – 110 001

GUIDELINES for India International Trade Fair (IITF), New Delhi

Architectural Guidelines:

Δ	RARE	SCHEME	FOR	INDIV	ΙΔΙΙΠΙ	STAI	ı s.
л.	DAIL	SCHILIVIL	1 011		IDUAL	JIAL	LJ.

- 1. All necessary documents must be submitted to Architecture Division
- 9. To prevent glass impact injuries at locations where Sill Height is <0.75m, use only Toughened/ Laminated safety glass or provide residual protection. In Horizontal or sloped glazing or glass used as balustrade, parapet or a railing, only Laminated safety glass to be used.
- 10. Clear glass panels capable of being mistaken for an unimpeded path of travel should be marked to make them visible by incorporating manifestation.
- 12. a. A team of ITPO shall visit all stalls and penalty deemed fit may be imposed on the participant in case of violation/deviation of any ITPO rule.
 - d. Compliance to all Architectural & Engineering guidelines (Annexure-B) shall be confirmed before starting construction.

B. STATE/MINISTRY/BOARD PAVILIONS INSIDE ITPO HALLS: (Page 3)

- 1. All necessary documents must be submitted to Architecture Division
- 6. To prevent glass impact injuries at locations where Sill Height glass used as balustrade, parapet or a railing, only Laminated safety glass to be used.
- 7. Clear glass panelsmarked to make them visible by incorporating manifestation.
- 8. Compliance to all Architectural & Engineering guidelines (Annexure-B) should be confirmed before starting construction.
- 9. For any violation ITPO shall be free to take punitive action

III. PERMANENT STATE/MINISTRY PAVILIONS Guidelines: (Page 4)

Architectural Guidelines:

- 11. To prevent glass impact injuries at locations only Laminated safety glass to be used.
- 12. Clear glass panelsmarked to make them visible by incorporating manifestation.
- 13. Compliance to all Architectural & Engineering guidelines (Annexure-B) should be confirmed before starting construction.
- 14. For any violation ITPO shall be free to take punitive action